



QUEST ELITE 4000

4-FLAVOR POST-MIX
DISPENSER

Also Included!



Multi-Panel Merchandiser

Unit Includes iced tea, lemonade, cold brew and a variety of latte graphics!



Single-Panel Merchandiser

Unit Includes juice graphic!



FEATURES

Wide product/ratio capability – Handles a wide range of post-mix products including juices with pulp, teas and cold coffees

Frost-free refrigeration compartment – Safely accommodates frozen, ambient or aseptic concentrate containers or BIB's

Large 14-16lb ice bank – Provides cold drinks during peak demand

Patented mixing system – Delivers consistent quality drinks with no stratification, slugging or dripping


LED illuminated graphics – Eliminates lost sales due to 'lights out' and reduces life costs

Narrow footprint – Conserves counter space

Easy to service – Modular component design and ease of access speeds service

'Sold out' indication – Alerts operator to product out condition and maximizes sales

Flexible Merchandiser – Option of single-panel or multi-panel merchandiser



PART NUMBER	DESCRIPTION
721414201JU1	Quest Elite 4 flavor, illuminated, flush, sold out push button 230/50, single-panel merch.
721414211JU1	Quest Elite 4 flavor, illuminated, flush, sold out portion control 230/50, single-panel merch.
720404101JU1	Quest Elite 4 flavor, illuminated, non-flush, push button 115/60, single-panel merch.
721404101JU2	Quest Elite 4 flavor, illuminated, non-flush, push button 115/60, multi-panel merch.
729011003	Extended Splash Panel Kit for Pitchers/Carafes
720401107	Refillable Concentrate Reservoir 3.5 L
729011152	Cup Locator
729011125	Bag-In-Box Option Kit
729011220	Portion Control Kit - 4 Flavor
729011183	Extender Nozzle Kit
629097145	ADA Installation Kit - 2 Flavor

TECHNICAL SPECIFICATIONS

REFRIGERATION	Hermetically sealed system, R-134a refrigerant 6.3 oz (180 g)
ICE BANK	14-16lb
CABINETRY	High impact plastic cabinetry with stainless steel front panel
DISPENSER DIMENSIONS	34"H x 15.2"W x 24.9"D (86.4 cm x 38.6 cm x 63.2 cm)
WEIGHT	Dry: 120 lb (54.4 kg) Operating: 185 lb (83.9 kg)
RECOMMENDED CLEARANCE	Back: 4" (10.16 cm) Top: 12" (30.48 cm) Sides: 4" (10.16cm)
WATER CONNECTION	0.375" (0.95 cm) SAE male flare SAE fitting on dispenser
CONCENTRATE STORAGE	Four 3.5 L bottles

WATER SUPPLY REQUIREMENTS

OPTIMUM SUPPLY SPECIFICATION . . 50psi(3.4 bar) flowing 3oz/sec

MAXIMUM STATIC PRESSURE . . 60psi (4.1 bar)

MINIMUM STATIC PRESSURE . . . 30psi (2.1 bar)

For water pressure exceeding the optimum supply
specification, flow control set at 50psi is recommended

COOLING Three 12 oz drinks/min
(355 mL) @ 75°F (24°C) ambient,
75°F (24°C) incoming water,
and 41°F (4°C) concentrate w/o
exceeding a 40°F (4°C)

FLOW RATE Adjustable water flow rate
from 1-2.2 oz/sec

AGENCY LISTINGS   

